

Pxxx0S3G-A Series

High Surge Current SIDACtor® - DO-214AB



Agency Approvals

Agency	Agency File Number
	E133083

Schematic Symbol



Description

The automotive grade Pxxx0S3G-A series DO-214AB protection thyristors are components designed to protect AC power line located in hostile environments from overvoltage transients.

The Pxxx0S3G-A series protect exposed interfaces in industrial and ICT applications, such as RS-485 data interfaces or AC and DC power supplies. These components switching voltage V_S are much lower than alternative component.

Designed to withstand a 4.0 kV (1.2/50 voltage, 8/20 current) combination wave surge per IEC 61000-4-5 and provide both overcurrent and overvoltage protection for the AC line.

Features and Benefits

- High reliability application and automotive grade AEC-Q101 qualified
- High surge rating 8/20 μs 2000 A protection
- High surge SIDACtor designed in a surface mount and compact DO-214AB package
- Low voltage overshoot
- Low on-state voltage
- Fails short circuit when surged in excess of ratings
- Whisker test is conducted based on JEDEC JESD201A per its table 4a and 4c pass class 1/1A/2
- IEC 61000-4-2 ESD 30 kV(Air), 30 kV (Contact)
- UL recognized compound meeting flammability rating V-0
- Component properties do not degrade after multiple surge events within its limits
- RoHS compliant and Halogen-free
- Pb-free E3 means 2nd level interconnect is Pb-free and the terminal finish material is tin (Sn) (IPC/JEDEC J-STD609A.01)
- Recognized to UL 497B as an isolated loop circuit protector

Applicable Global Standards

- TIA-968-A
- TIA-968-B
- ITU K.20/21 Enhanced Level
- ITU K.20/21 Basic Level
- GR 1089 Intra-building
- IEC 61000-4-5, 2nd edition
- YD/T 1082
- YD/T 993
- YD/T 950

Electrical Characteristics

Part Number	Marking	V_{DRM}	V_S	I_H	I_S	I_T	V_T	Capacitance	
		@ $I_{DRM} = 5 \mu A$	@ 100 V/ μs	mA min	mA max	A max	@ $I_T = 2.2 A$	@ 1 MHz, 2 V bias	pf min
P2600S3GLRP-A	P26G	220	300	50	800	2.2	4	150	450
P3100S3GLRP-A	P31G	275	350	50	800	2.2	4	150	450
P3500S3GLRP-A	P35G	320	400	50	800	2.2	4	150	450
P3800S3GLRP-A	P38G	350	430	50	800	2.2	4	150	450

Notes:
 - Absolute maximum ratings measured at $T_A = 25^\circ C$ (unless otherwise noted).
 - Components are bi-directional (unless otherwise noted).

Pxxx0S3G-A Series

High Surge Current SIDACtor® - DO-214AB

Surge Ratings

Series	I_{PP}	I_{TSM} 50 / 60 Hz	di/dt
	8/20 ¹ 1.2/50 ²		
	A min		
G	2000	250	420

Notes:


1. Current waveform in μ s
2. Voltage waveform in μ s

- Peak pulse current rating (I_{pp}) is repetitive and guaranteed for the life of the product.


Thermal Considerations

Package	Symbol	Parameter	Value	Unit
DO-214AB 	T_J	Operating Junction Temperature Range	-65 to +125	°C
	T_S	Storage Temperature Range	-65 to +150	°C
	$R_{\theta JA}$	Thermal Resistance: Junction to Ambient	75	°C/W


V-I Characteristics




tr x td Pulse Waveform



Normalized V_S Change vs. Junction Temperature




Normalized DC Holding Current vs. Case Temperature



Pxxx0S3G-A Series

High Surge Current SIDACtor® - DO-214AB

Peak Surge Current Derating Curve




Physical Specifications


Weight	0.007 ounce, 0.21 grams
Case	JEDEC DO214AB. Molded component over glass passivated junction
Polarity	Uni-directional products are denoted with a cathode band
Terminal	Matte tin-plated leads, solderable per JESD22-B102

Soldering Parameters


Reflow Condition	Pb-free assembly (see Fig. 1)	
Pre Heat	- Temperature Min ($T_{s(min)}$)	+150 °C
	- Temperature Max ($T_{s(max)}$)	+200 °C
	- Time (Min to Max) (t_s)	60-120 secs.
Average Ramp Up Rate (Liquidus Temp (T_L) to Peak)	3 °C/sec. max.	
$T_{s(max)}$ to T_L - Ramp-up Rate	3 °C/sec. max.	
Reflow	- Temperature (T_L) (Liquidus)	+217 °C
	- Temperature (t_L)	60-150 secs.
Peak Temp (T_p)	+260 (+0/-5) °C	
Time Within 5 °C of Actual Peak Temp (t_p)	30 secs. max.	
Ramp-down Rate	6 °C/sec. max.	
Time 25 °C to Peak Temp (T_p)	8 min. max.	
Do Not Exceed	+260 °C	



Part Marking



Part Numbering




Environmental Specifications

High Temp Voltage Blocking	80 % rated V_{DRM} ($V_{AC Peak}$) +125 °C, 504 or 1008 hrs. MIL-STD-750 (Method 1040) JEDEC, JESD22-A-101
Temp Cycling	-65 °C to +150 °C, 15 min. dwell, 10 up to 100 cycles. MIL-STD-750 (Method 1051) EIA/JEDEC, JESD22-A104
Biased Temp & Humidity	80 % rated V_{DRM} (+85 °C) 85 %RH, and not exceed 100 V or limit of chamber. 504 up to 1008 hrs. EIA/JEDEC, JESD22-A-101
High Temp Storage	+150 °C 1008 hrs. MIL-STD-750 (Method 1031) JEDEC, JESD22-A-101
Low Temp Storage	-65 °C, 1008 hrs.
Unbiased HAST	96 hrs. at $T_A = 130$ °C/85 %RH or 264 hrs. at $T_A = 110$ °C/85 %RH. TEST before and after UHAST, JEDEC, JESD22-A-118
Resistance to Solder Heat	+260 °C, 30 secs. MIL-STD-750 (Method 2031)
Moisture Sensitivity Level	85 %RH, +85 °C, 168 hrs., 3 reflow cycles (+260 °C Peak). JEDEC-J-STD-020, Level 1

Pxxx0S3G-A Series

High Surge Current SIDACtor® - DO-214AB

Dimensions – DO-214AB




Dimensions	Inches		Millimeters	
	Min	Max	Min	Max
A	0.114	0.126	2.900	3.200
B	0.260	0.280	6.600	7.110
C	0.220	0.245	5.590	6.220
D	0.079	0.103	2.060	2.620
E	0.030	0.060	0.760	1.520
F	-	0.008	-	0.203
G	0.305	0.320	7.750	8.130
H	0.006	0.012	0.152	0.305
I	0.129	-	3.300	-
J	0.094	-	2.400	-
K	-	0.165	-	4.200
L	0.094	-	2.400	-

Packing Options

Part number	Component Package	Quantity	Packaging Option	Packaging Specification
Pxxx0S3GLRP-A	DO-214AB	3000	Tape & Reel - 16 mm tape/13" reel	EIA STD RS-481

Tape and Reel Specification – DO-214AB



Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at <http://www.littelfuse.com/disclaimer-electronics>.