

Features

- Dual Voltage-Tracking Protectors
- Wide negative pressure range: $V_{MGL} = -167\text{ V max}$
- Low dynamic switching voltages: V_{FP} and V_{DGL}
- Low gate triggering current: $I_{GT} = 5\text{ mA max}$
- Peak pulse current: $I_{PP} = 50\text{ A (10/700}\mu\text{s)}$
- Holding current: $I_H \geq 150\text{ mA}$

Applications


P61089B is designed to protect communication equipment such as SPC exchanger from damaging overvoltage transients in the second level

Mechanical Date

- Package: SOP-8
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free
- Terminals: Tin plated leads, solderable per J-STD-002 and JESD22-B102

Dual Programmable Thyristor Transient Voltage Suppressor


SOP-8




DIMENSIONS

DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.053	0.069	1.35	1.75	
B	0.004	0.010	0.10	0.25	
C	0.053	0.061	1.35	1.55	
D	0.013	0.020	0.33	0.51	
E	0.007	0.010	0.17	0.25	
F	0.185	0.200	4.70	5.10	
G	0.050		1.270		TYP.
H	0.228	0.244	5.80	6.20	
J	0.150	0.157	3.80	4.00	
K	0.016	0.050	0.40	1.27	
θ	0°	8°	0°	8°	

Suggested Solder Pad Layout



Internal Structure and Marking Code



Testing Standards

Type	Vave sharp		ITSP
ITU-T K.20/21 and K.45	Voltage	10/700μs	50A
	Current	5/310μs	

Maximum Ratings

Parameter	Symbol	Value	Unit
Non-repetitive peak pulse voltage ^(Note 1)	V_{PP}	2000	V
Non-repetitive peak pulse current ^(Note 2)	I_{PP}	50	A
Non repetitive surge peak on-state current (60 Hz sinusoidal)	$t_p = 500ms$	6.5	A
	$t = 1s$	4.6	
Maximum voltage (Line to GND)	V_{MLG}	-170	V
Maximum voltage (Gate to Line)	V_{MGL}	-167	V
Storage temperature range	T_{stg}	-55~150	°C
Junction temperature	T_j	150	°C
Maximum temperature for soldering during 10s	T_L	260	°C

Note: 1、10/700μs means voltage wave, and its rise time is 10μs, fail time is 700μs;
2、5/310μs means current wave, and its rise time is 5μs, fail time is 310μs。

Electrical Characteristics @ 25°C (Unless Otherwise Specified)

Symbol	Parameter
V_F	Line-ground voltage
V_{FP}	Line-ground peak voltage
I_{GT}	Gate trigger current
I_H	Holding current
V_{GT}	Gate-cathode trigger voltage
I_{RG}	Gate-line reverse leakage current
V_{DGL}	Gate-line dynamic switching voltage
I_R	Line-ground reverse leakage current
V_{GATE}	Gate-ground voltage
C	Line-ground off state capacitance




Figure 1. Voltage-Current Characteristic
Unless Otherwise Noted, All Voltages are Referenced to the Anode

Electrical Characteristics @ 25°C (Unless Otherwise Specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Line-ground diode parameters						
Forward voltage	V_F	$I_F=5A$, $T_P=500\mu s$			3	V
Peak forward voltage ⁽¹⁾	V_{FP}	10/700 μs , 1.5kV, $R_P=10\Omega$			5	V
Thyristor parameters						
Gate trigger current	I_{GT}	$V_{GND-LINE}=-100V$	0.1		5	mA
Holding current ¹⁾	I_H	$V_{GATE}=-100V$	150			mA
Gate trigger voltage	V_{GT}	$V_{GND-LINE}=-100V$			2.5	V
Gate-Line Reverse leakage current	I_{RG}	$T_C=25^\circ C$ $V_{RG}=-170V$			5	μA
		$T_C=70^\circ C$ $V_{RG}=-170V$			50	
Gate-Line Dynamic switching voltage ⁽²⁾	V_{DGL}	$V_{GATE}=-100V$ 10/700 μs , 1.5kV, $R_P=10\Omega$			10	V
Thyristor and diode parameters						
Line-GND Reverse leakage current	I_R	$T_C=25^\circ C$ $V_{GATE/LINE}=-1V$ $V_{RM}=-167V$			5	μA
		$T_C=70^\circ C$ $V_{GATE/LINE}=-1V$ $V_{RM}=-167V$			50	
Line-GND off state capacitance	C	$V_R=-3V$, F=150KHz			100	pF
		$V_R=-48V$, F=150KHz			50	

Note: 1、 R_P is the protective resistance mounted on the card.
 2、Don't make record if fluctuation time is less than 50ns.

Ordering Information

Device	Packing
Part Number-TP	Tape&Reel: 4Kpcs/Reel

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp.* does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp.* and all the companies whose products are represented on our website, harmless against all damages. *Micro Commercial Components Corp.* products are sold subject to the general terms and conditions of commercial sale, as published at <https://www.mccsemi.com/Home/TermsAndConditions>.

*****LIFE SUPPORT*****

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

*****CUSTOMER AWARENESS*****

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.