

## DATASHEET

# PIM400 Series; ATCA Board Power Input Modules

**-36 to -75 Vdc; 400W/10A**

**9Vdc – 36Vdc input; +15V, -15V Dual Output, 0.3A 9W Output**



## Description

The PIM400 series of Power Input Modules are designed to greatly simplify the task of implementing dual redundant, hot swap –48Vdc power distribution with EMI filtering on an ATCA or other telecom boards. The PIM400 with optional I<sup>2</sup>C digital interface capability, when used with a variety of OmniOn's series of Bus converters (Barracuda™ Series) /POLs (DLynx™ Series) provides for a quick, simple and elegant power solution to a wide variety of demanding & intelligent power system architectures.

## Applications

- ATCA Front Board / Blade
- Central Office Telecom equipment
- High availability server and storage applications

## Features

- -48V/10A Dual redundant input power distribution
- 3.3Vdc/3.6A & 5.0Vdc/150mA of isolated Management Power for IPM or other housekeeping functions
- Independent holdup capacitor charging voltage; trimmable from 50 to 95Vdc for optimal real estate
- OR'ing functionality, Inrush protection & hot swap capability
- Integral EMI filter designed for the ATCA board to meet CISPR Class B with minimal external filtering
- Protection: Reverse polarity, under voltage, input transient over voltage/current and temperature
- I<sup>2</sup>C digital interface options
- Isolated A/B Feed Loss /Open Fuse Alarm
- High efficiency : 98%

## Options

- Choice of short pin lengths
- I<sup>2</sup>C Digital Interface
- - 40 to 85°C ambient temperature operation
- Industry Standard Quarter brick size: 58.4 mm x 36.8 mm x 13.7 mm (2.3 in x 1.45 in x 0.54 in)
- MTBF : 2,308,563 hours per TELCORDIA
- Compliant to RoHS Directive 2011/65/EU and amended Directive (EU) 2015/863
- Compliant to REACH Directive (EC) No 1907/2006
- ANSI/UL# 62368-1 and CAN/CSA† C22.2 No. 62368-1 Recognized, DIN VDE‡ 0868-1/A11:2017 (EN62368-1:2014/A11:2017)
- Meets the voltage and current requirements for ETSI 300-132-2 and complies with and licensed for Basic insulation rating 2250 Vdc Isolation tested in compliance with IEEE 802.3 $\alpha$  PoE standards
- ISO\*\*9001 and ISO 14001 certified manufacturing facilities

See Footnote on Page No. 6

## Technical Specifications

### Absolute Maximum Ratings

Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. These are absolute stress ratings only, functional operation of the device is not implied at these or any other conditions in excess of those given in the operations sections of the data sheet. Exposure to absolute maximum ratings for extended periods can adversely affect the device reliability.

Parameter	Device	Symbol	Min	Typ	Max	Unit
Input Voltage						
Continuous	All	$V_I$	-0.5		-75	$V_{dc}$
Transient (Pulse duration = 1ms, square wave)	All	$V_{tr}$			-100	$V_{dc}$
Additionally: Transient Input Undervoltage, Overvoltage and Impulse per ANSI T1.315-2001 (R2006)	All					
Reverse Polarity Protection					+75V	$V_{dc}$
Holdup Capacitor						
Voltage (with respect to -48V_OUT)	All	$V_{HLDP}$	100		100	$V_{dc}$
Capacitance	All	$C_{HLDP}$			3300	$\mu F$
Temperature						
Normal Operating Ambient Temperature (See Thermal Considerations section)	All	$T_A$	-40		85	$^{\circ}C$
Storage Temperature	All	$T_{stg}$	-55		125	$^{\circ}C$
Isolation Voltage						
Input to MGMT_PWR Output Voltage & Alarm	All				2250	$V_{dc}$
Input to SHELF_GND Voltage	All				2250	$V_{dc}$
Input to LOGIC_GND Voltage	All				2250	$V_{dc}$


#### CAUTION:

1. This power module is not internally fused. Both A & B feeds and their corresponding returns must be individually fused.

To preserve maximum flexibility, internal fusing is not included. However, to achieve maximum safety and system protection, the safety agencies require a fast-acting fuse with a maximum rating of 20 Amps and Voltage Rating  $\geq 75V_{dc}$  for the -48AF, -48BF VRTN\_AF & VRTN\_BF feeds. Consult Fusing and fault protection Section of PICMG 3.0 ATCA specifications for additional information. Based on the information provided in this data sheet on inrush

# Technical Specifications (continued)

## ATCA Board Typical Application



### External Holdup Capacitor Selection

$$C_{HLDP} = \frac{2T_{HU}P_{HU}}{V_{HLDP}^2 - V_{UV}^2}$$

### External Holdup Trim Resistor Selection

$$R_{TRIM}(\Omega) = \left( \frac{500,000}{V_{HLDP} - 50.0} - 10,000 \right)$$

## Suggested Bill of Materials

(Note: Customer is ultimately responsible for the final selection and verification of the suggested parts for the end application).

Ref Des	Description (Values)	Comments
F1-F4	Fuses (15A)	Max fuse rating not to exceed 20A, fast acting
F5,F6	Fuses (15A)	0.5 to 1A rated
R1,R2	Pre-charge Resistors (15 Ohms)	High Surge Power Type e.g. KOA P/N SG73
R_TRIM	Resistor	See Design Consideration section for details
R_PULLUP	Resistor (3.3 kOhms)	Alarm pull-up resistor
C_FLTR	Capacitor(s) (100µF)	300 µF (max)
C_HLDP	Capacitor(s)	3300µF (max); see Design Consideration section for details
C_OUT	Capacitor(s)	Consult data sheet for the applicable DC/DC Bus Converter
C_EMI	Capacitors	See Design Consideration section for details

See Footnote on Page No. 6

## Technical Specifications (continued)

### Electrical Specifications

Unless otherwise indicated, specifications apply over all operating input voltage, resistive load, and temperature conditions.

Parameter	Device	Symbol	Min	Typ	Max	Unit	
<b>-48V Dual Feed Inputs (-48_AF,-48_BF,VRTN_AF,VRTN_BF)</b>							
Input Voltage Range	All	$V_I$	-36	-48	-75	Vdc	
Output Current With the following maximum power limits 400W @ 40Vin, 480W @ 48Vin, 540W @ 54Vin	All	$I_I$			10	Adc	
Disabled input current drain if input voltage falls below $V_{UVLO}$ for > 2 seconds.	All	$I_{UVLO}$		10		mA	
Enabled No-load input current	All	$I_{stdby}$		40	70	mA	
Inrush Transient (@ -48 VI, C_FLTR = 200 $\mu$ F & EARLY_A, EARLY_B Pre-charger resistors 15 ohms per leg as recommended in the "ATCA Board Typical Application" figure, p=2) Duration: 0.1ms to 0.9ms Duration: 0.9ms to 3 ms (Logarithmically declining)	All	$I_{pk}$ $I_{pk}$			40 40 to 18	Adc Adc	
<b>ENABLE A/B Signal Inputs (ENABLE_A, ENABLE_B)</b>							
Input Voltage Threshold (On/Off); Default Setting	All	$V_{UVHI}$ (On)	-33.5	-35.3	-36.0	Vdc	
		$V_{UVLO}$ (Off)	-32.4	-33.7	-34.1		
Enable A / B Signals current drain ( $V_{in} = -48Vdc$ )	All			380		$\mu$ Adc	
<b>Main Output (-48V_OUT, VRTN_OUT)</b>							
Efficiency ( $V_{in} = -48V$ ; 3.3V/5.0V @ no load) 400W Output Power 300W Output Power	All	$\eta$		98.2		%	
	All	$\eta$		98.5		%	
Output Voltage Delay	All	$T_{delay}$		100		ms	
Input Current Limit	All	$I_{limit}$	11	13	15	A	
External Output Filter Capacitance (C_FLTR)	All	C_FLTR	80	100	300	$\mu$ F	
<b>Holdup Capacitor Output Voltage (V_HLDP)</b>							
Holdup Capacitor Voltage Trim Range	All	$V_{HLDP}$	50	90	95	V	
Holdup Capacitor Output Voltage Tolerance @ $V_{HLDP} = 90Vdc$			+6		-6	%	
-48V_OUT Threshold					40.0		
To charge external holdup capacitors (C_HLDP)					-36.0		
To discharge external holdup capacitors (C_HLDP)							
dV/dt on Hold-up Connect					80		V/ms
Switching Frequency		f		330		kHz	
<b>A/B Feed Loss / Fuse Alarm Output (ALARM)</b>							
ALARM ON Input Voltage Threshold	All		-36.4	-37.2	-40.4	Vdc	
ALARM OFF Input Voltage Threshold				-40.5		Vdc	
External Pull-up Voltage					5.0	Vdc	

See Footnote on Page No. 6

## Technical Specifications (continued)

### Electrical Specifications (Continued)

Parameter	Output Voltage	Symbol	Min	Typ	Max	Unit
<b>+3.3V Isolated Management Power Output (+3V3)</b>						
Input Under-Voltage Lockout Turn-On Voltage Threshold	All		-32.4	-33.7 -34.5	-34.1	V
Total Output Voltage Range (Over all operating input voltage, resistive Load and temperature conditions until end of life).	All	+3V3	3.170	3.350	3.430	V
Output Current	All	$I_o$	0	-	3.6	Adc
Output Ripple and Noise Measured across 10 $\mu$ F ceramic capacitor $V_I = V_{I,nom}$ $T_A = 25^\circ\text{C}$ , $I_o = I_{o,max}$ RMS (500 MHz bandwidth) Peak-to-peak (500MHz bandwidth)	All		- -	16 75	50 200	mVrms mVp-p
Output Current- Limit Inception	All	$I_{o,lim}$	-	4	6	Arms
Output Short-circuit Current	All	$I_{o,sc}$	-	3	-	Arms
External Load Capacitance	All	$C_{O,max}$	0	-	1000	$\mu$ F
Switching Frequency	All	f		330		kHz
Dynamic Response ( $di/dt = 0.1\text{A}/\mu\text{s}$ , $V_{lin} = V_{in,nom}$ , $T_A = 25^\circ\text{C}$ ) Load change from $I_o = 50\%$ to $75\%$ of $I_{o,max}$ , Peak Deviation Settling Time ( $V_o < 10\%$ of peak deviation)	All	$V_{pk}$ $t_s$		7 800		%, $V_{o, set}$ $\mu\text{s}$
Turn-On Delay ( $I_o = 80\%$ of $I_{o,max}$ , $T_A = 25^\circ\text{C}$ )	All	$T_{delay}$		50		$\mu$
Output voltage overshoot ( $I_o = 80\%$ of $I_{o,max}$ , $V_I = 48\text{Vdc}$ $T_A = 25^\circ\text{C}$ )	All				3%	%, $V_{o, set}$
Output Over Voltage Protection	All	$V_{o, limit}$	3.7		5.4	V
<b>+5.0V Isolated Management Power Output (+5V0)</b>						
Total Output Voltage Range (Over all operating input voltage, resistive Load and temperature conditions until end of life).	All	+5V0	4.80	5.00	5.20	V
Output Current	All	$I_o$	0	-	150	mAdc
Output Current-Limit Inception	All	$I_{o,lim}$	-	250	-	mA
Output Short-circuit Current	All	$I_{o,sc}$	-	150	-	mARMS
External Load Capacitance	All	$C_{O,max}$	0	-	1000	$\mu$ F
Switching Frequency	All	f	-	330	-	kHz

See Footnote on Page No. 6

## Technical Specifications (continued)

### Digital Interface Specifications

Unless otherwise indicated, specifications apply over all operating input voltage, resistive load, and temperature conditions. See Feature Descriptions for additional information.

Parameter	Conditions	Symbol	Min	Typ	Max	Unit
<b>Digital Signal Interface Characteristics</b>						
Clock frequency range		$f_{CLK}$		100	400	kHz
Measurement Tolerance						
Feed Voltage A/B (-48V_AF & -48V_BF)				+/-3		%
Holdup Voltage (V_HLDP)				+/-3		%
-48V_OUT current (-48V_IOUT)	% of $I_{O,max}$			+/-3		%
Module Temperature (TEMP)				+/-3		°C

### General Specifications

Parameter	Device	Min	Typ	Max	Unit
Calculated MTBF ( $P_o=0.8P_{o,RATED}$ , $48V_{IN}$ , $T_A=40^{\circ}C$ , Airflow=300LFM) Telecordia Issue 2 Method 1 Case 3	All		2,308,563		Hours
Weight		-	28.3 (1.0)	-	g (oz.)

#### FOOTNOTES

UL is a registered trademark of Underwriters Laboratories, Inc.

† CSA is a registered trademark of Canadian Standards Association.

‡ VDE is a trademark of Verband Deutscher Elektrotechniker e.V.


\*\* ISO is a registered trademark of the International Organization of Standards

⌘ IEEE and 802 are registered trademarks of the Institute of Electrical and Electronics Engineers, Incorporated.

# Technical Specifications (continued)

## Characteristic Curves


The following figures provide typical characteristics for the PIM400X modules at 25°C.



TIME, t (2ms/div)

Figure 1. Inrush Current  
CH2: VRTN\_OUT wrt -48Vout (Vo)  
CH4: Input current (IIN)


Test Conditions:  
48V<sub>in</sub>, 400W, C<sub>FLTR</sub> = 100uF



TIME, t (200µs/div)

Fig 2: Input Transient on one feed  
CH1: Feed B step to 60V (20V/Div)  
CH2: Feed A at 48V (20V/Div)  
CH3: VRTN\_OUT (20V/Div)


Test Conditions:  
Full load



TIME, t (2ms/div)

Fig 3: Hold-up Event vs 3.3Vout  
CH1: Feed A (20V/Div)  
CH2: Hold-up Voltage (20V/Div)  
CH3: VRTN\_OUT (20V/Div)  
CH4: 3.3Vout (2V/Div)

Test Conditions:  
1. Payload Bus Converter: QBVW033A0B  
2. Load: 12.0V Bus Converter Output @ 33A;  
3.3V@3.6A  
3. C<sub>Hold-up</sub> = 2200 µF  
4. C<sub>FLTR</sub>=220µF  
5. V<sub>HLDP</sub>=90V



TIME, t (2ms/div)


Fig 4: Hold-up Event vs 12.0Vout  
CH1: Feed A (20V/Div)  
CH2: Hold-up Voltage (20V/Div)  
CH3: VRTN\_OUT (20V/Div)  
CH4: 12.0 Vout (5V/Div)

Test Conditions:  
1. Payload Bus Converter: QBVW033A0B  
2. Load: 12.0V Bus Converter Output @ 33A;  
3.3V@3.6A  
3. C<sub>Hold-up</sub> = 2200 µF  
4. C<sub>FLTR</sub>=220µF  
5. V<sub>HLDP</sub>=90V

## Technical Specifications (continued)

### Characteristic Curves (continued)


The following figures provide typical characteristics for the PIM400X modules at 25°C.



TIME, t (20ms/div)

**Fig 5: Turn- ON Threshold**


CH1: Input Voltage (20V/Div)  
CH2: VRTN\_OUT voltage (20V/Div)  
CH4: Input Current (5A/Div)



TIME, t (10ms/div)

**Fig 6: Turn- OFF Threshold**

CH1: Input Voltage (20V/Div)  
CH2: VRTN\_OUT voltage (20V/Div)  
CH4: Input Current (2A/Div)




TIME, t (10ms/div)

**Fig 7a: Line Transient performance per ANSI T1.315-2001 standard vs +12.0V output**

CH1: +12Vout voltage (5V/Div)  
CH3: -48V input Voltage (20V/Div)  
Test Conditions:

1. PIM400 + QBDW033A0 (12V Bus Converter)
2. Load: +12Vout @ 30A; 3.3V @ 3.0A
3. C\_HLDP = 2200  $\mu$ F
4. C\_FLTR) = 220  $\mu$ F



TIME, t (10ms/div)

**Fig 7b: Line Transient performance per ANSI T1.315-2001 standard vs 3.3V output**


CH2: +3V3 Output Voltage (1V/Div)  
CH3: -48V input Voltage (20V/Div)  
Test Conditions:

5. PIM400 + QBDW033A0 (12V Bus Converter)
6. Load: +12Vout @ 30A; 3.3V @ 3.0A
7. C\_HLDP = 2200  $\mu$ F
8. C\_FLTR) = 220  $\mu$ F


## Technical Specifications (continued)

### Characteristic Curves (continued)


The following figures provide typical characteristics for the PIM400X modules at 25°C.




**Fig 8 a: Efficiency vs Output Current**  
**Test Conditions:**  
 No load on 3.3V output



**Fig 8b: Power Dissipation vs Output Current**  
**Test Conditions:**  
 No load on 3.3V output



**Fig 9 a: Efficiency**  
**Test Conditions:**  
 Full load on 3.3V output




**Fig 9 b: Power Dissipation**  
**Test Conditions:**  
 Full load on 3.3V output

## Technical Specifications (continued)

### Characteristic Curves (continued)


The following figures provide typical characteristics for the PIM400X modules at 25°C.



TIME, t (0.500ms/div)

Fig 10: 3.3V Turn-On


Test Conditions:  
Cout=10μF ceramic



TIME, t (500μs/div)

Fig 11: 3.3V Load Transient


Test Conditions:  
Cout =10μF ceramic  
Step Load Change = 50%-75%-50% of Iout,max  
Slew Rate = 1 Aμs



TIME, t (2 μs/div)

Fig 12: 3.3V Ripple

Test Conditions:  
Cout=10μF ceramic  
Iout=3.6A




TIME, t (5ms/div)

Fig 13: ALARM Output change of state with input voltage dropout

## Technical Specifications (continued)

### PIM400 Internal Block Diagram



### PIN FUNCTIONS

Pin No.	Signal Name	Description
1	-48V_AF	-48V_A Feed (Externally Fused)
2	-48V_BF	-48V_B Feed (Externally Fused)
3	VRTN_AF	VRTN_A Feed (Externally Fused)
4	VRTN_BF	VRTN_B Feed (Externally Fused)
5	ENABLE_AF	ENABLE_A Feed (Externally Fused) (Short Pin, connected to VRTN_A on the back plane)
6	ENABLE_BF	ENABLE_B Feed (Externally Fused) (Short Pin, connected to VRTN_B on the back plane)
7	SHELF_GND	Shelf / Chassis / Safety Ground
8	+5V0	Isolated 5.0Vdc (Blue LED Power) w.r.t. LOGIC_GND
9	+3V3	Isolated 3.3Vdc (Management Power) w.r.t. LOGIC_GND
10**	ADD	I2C Address w.r.t. LOGIC_GND
11**	DAT	I2C Data w.r.t. LOGIC_GND
12**	CLK	I2C Clock w.r.t. LOGIC_GND
13	LOGIC_GND	Logic / Secondary / Isolated Ground
14	ALARM	Opto-isolated -48V A/B Feed Loss or Open Fuse Alarm (w.r.t LOGIC_GND)
15	-48V_OUT	OR'd and Inrush protected -48V Output Bus
16	TRIM_HLDP	Holdup capacitor output voltage trim w.r.t. -48V_OUT
17	VRTN_OUT	OR'd and Inrush protected VRTN Output Bus
18	V_HLDP	+ve terminal connection point for Holdup capacitor

\*\* Pins 10, 11 & 12 are present only on modules with I<sup>2</sup>C digital interface option (-K)

## Technical Specifications (continued)

### Feature Descriptions

#### Introduction

The PIM400X module is designed to support the Advanced Telecommunications Computing Architecture (ATCA) power entry distribution requirements for the Front Board / Blade per the PICMG 3.0 specifications.

The PICMG 3.0 specification defines the Mechanical, Shelf Management Interface, Power Distribution, Thermal, Data I/O and Regulatory requirements for the next generation of modular telecom architecture platform for use in Central Office telecom environments.

#### Input Pin Connections

The ATCA board is specified to accept up to a maximum of 400W of input power via dual, redundant -48Vdc Feeds through the Zone 1 (Power and Management) connector, designated P10. The power connector provides board to backplane engagement via pins of varying lengths. Please consult the PICMG 3.0 specifications for details.

The following are the design considerations of the input pin connections of the PIM400X to the ATCA power connector.

From ATCA (P10 Connector)		Connection Requirement	To PIM400X	
Pin #	Pin Designation		Pin #	Signal Designation
33	-48V_A	Via Fuse(F3)	1	-48V_AF
34	-48V_B	Via Fuse(F4)	2	-48V_BF
28	VRTN_A	Via Fuse(F1)	3	VRTN_AF
29	VRTN_B	Via Fuse(F2)	4	VRTN_BF
30	EARLY_A	Via Resistor(R1) *		-48V_A
31	EARLY_B	Via Resistor(R2) *		-48V_B
32	ENABLE_A	Via Fuse(F5)	5	ENABLE_AF
27	ENABLE_B	Via Fuse(F6)	6	ENABLE_BF
25	SHELF_GND	Direct	7	SHELF_GND
26	LOGIC_GND	Direct	11	LOGIC_GND

\* Pre-charge resistors

The first pins to mate in the ATCA power connector are the EARLY\_A, EARLY\_B, the two grounds (LOGIC\_GND, SHELF\_GND) and the two returns (VRTN\_A, VRTN\_B); followed by staggered connections of -48V\_A and -48V\_B power Feeds. The last pins to engage are the two short pins, ENABLE\_A & ENABLE\_B. The ATCA backplane connects the ENABLE\_A to VRTN\_A, ENABLE\_B to VRTN\_B, EARLY\_A to -48V\_A and EARLY\_B to -48V\_B. EARLY\_A & EARLY\_B Connections: During hot insertion of the ATCA board, the Inrush Control circuit limits the surge current to the C\_FLTR capacitor. However, due to the presence of a small amount of internal EMI filter capacitance (located before the Inrush Control circuit), it is recommended that

Precharge resistors, R1 & R2 (100 Ohms, with appropriate surge capability) be connected as shown in the Typical Application circuit.

#### Output Pin Connections (Standard Module: PIM400Z)

The output pin connections of the PIM400X to the system board are described below:

From PIM400X		To ATCA Front Board		Notes
Pin #	Pin Designation	Terminal	Component	
15	-48V_OUT	Vin(-)	DC/DC	(1)
17	VRTN_OUT	Vin(+)	DC/DC Converter	
18	V_HLDP	+ve	Holdup	(2)
16	TRIM_HLDP	RTrim	Holdup	
8	+5V0		Management Power	(3)
9	+3V3			
14	ALARM	R <sub>pull-up</sub>	IPM/System	(4)

#### Additional Output Pin Connections (Modules with optional I<sup>2</sup>C Digital Interface: Option - K)

The following additional output pins of the PIM400KZ available for I<sup>2</sup>C Digital Interface to the IMP/System Controller are defined below:

From PIM400KZ		To ATCA Front Board		Notes
Pin #	Pin Designation	IPM/System Controller Interface	I <sup>2</sup> C	
10	ADD		I2C Address w.r.t. LOGIC_GND	(5)
11	DAT		I2C Data w.r.t. LOGIC_GND	
12	CLK		I2C Clock w.r.t. LOGIC_GND	

#### Inrush Current Control / Hot Plug Functionality

The module provides inrush current control / hot plug capability. The peak value of the inrush current and the duration complies with the PICMG 3.0's Inrush Transient specifications. The specifications shall be met with the external C\_HLDP and C\_FLTR capacitances as specified in the previous sections. The unique design of the module where the large energy storage capacitors are segregated from the input filter capacitors allows the module to meet the stringent PICMG's inrush transient specifications with minimal energy storage capacitors.

## Technical Specifications (continued)

### Design Considerations

#### -48V Main Output Bus:

(Signal Names: -48V\_OUT & VRTN\_OUT)

This is the main -48V output bus that provides the payload power to the downstream (one or more) DC/DC converters. The PIM400X module does not regulate or provide isolation from the input -48V A/B feeds.

The main functionality of the module is to provide -48V A/B Feeds OR'ing, inrush protection for hot swap capability and EMI filtering to attenuate the noise generated by the downstream DC/DC converters.

- The -48V\_OUT pin connects to the Vin(-) pin and the VRTN\_OUT pin connects to the Vin(+) pin of the DC/DC converter (s).
- The -48V\_OUT bus may require a fuse depending on the power and fusing requirements of the DC/DC converter.
- Input filtering of the DC/DC converter is provided by C\_FLTR close to the input pins of the DC/DC converter (s); additional high frequency decoupling ceramic capacitors (0.01 to 0.1µF are recommended for improved EMI performance.
- The maximum C\_FLTR capacitance across all the downstream DC/DC converters should not exceed 300µF.
- The minimum C\_FLTR capacitance (80µF) recommendation is based on meeting the EMI requirements.

#### Holdup Capacitor Output Voltage (V\_HLDP)

This output provides the user settable high voltage to charge the C\_HLDP capacitor (s) to allow the ATCA board to meet the 5ms, 0Volts transient requirements.

- The V\_HLDP pin connects to the +ve terminals of the C\_HLDP capacitors while the -ve terminals of the C\_HLDP connects to the -48V\_OUT bus.
- The C\_HLDP capacitance is dependent on the system power and the holdup time requirements based on the following formula

$$C_{HLDP} = \frac{2T_{HU}P_{HU}}{V_{HLDP}^2 - V_{UV}^2}$$

Where  $T_{HU}$  is the desired holdup time,  $P_{HU}$  is the holdup power drawn from the holdup capacitors (=input power of the downstream DC/DC bus converter + Management Power),  $V_{HLDP}$  is the trimmed holdup capacitor voltage and  $V_{UV}$  is the undervoltage lockout threshold of either the

downstream bus or the Management Power DC/DC converter (higher of the two).

#### Holdup Capacitor Trim Voltage (TRM\_HLDP)

The resistor R\_TRIM sets the external holdup capacitor voltage to the desired setting. The output voltage is adjustable from 50 to 90V. The resistor, R\_TRIM is selected by the following equation:

$$R_{TRIM}(\Omega) = \left( \frac{500,000}{V_{HLDP} - 50.0} - 10,000 \right)$$

#### High Voltage Discharge Mechanism:

Per the PICMG 3.0 specifications, the PIM400 provides an internal discharge mechanism to discharge the holdup/bulk capacitance to less than -60Vdc and less than 20 joules within one second of disconnection from the backplane.

#### Management Power (+3V3, +5V0)

Two isolated secondary output voltages (+3V3 & +5V0) are provided for ATCA Front Board's IPM/System Controller (3.3V) and for the Blue LED's (5.0V) power requirements. Both the outputs are referenced to LOGIC\_GND.

- The management power is available even when the input voltage is down to -36Vdc.
- No additional output capacitors are required, but a 22µF tantalum/ceramic and a 0.01 to 0.1µF ceramic capacitors are highly recommended to contain the switching ripple and noise.


#### Input Fault Alarm Signal (ALARM)

Both the input feeds, -48V\_AF & -48V\_BF are monitored via the -48V\_ALARM signal. In the event of a loss of power from either feeds (-48V\_A or -48V\_B) or the opening of their respective fuses, the -48V\_ALARM shall change its logical state indicating a fault. During normal operation, the signal is Low. During fault condition, the alarm signal shall assume a HI state when the ALARM pin is pulled up to an external pull voltage (maximum 5.0V) via an external pullup resistor ( $R_{Pullup}$ ). The ALARM output is internally referenced to the LOGIC\_GND. A 3.3K pull up resistor to 3.3V Management Power should suffice.


## Technical Specifications (continued)

### EMI Filtering

The module incorporates an EMI filter that is designed for the ATCA board to help meet the conducted emissions requirements of CISPR 22 Class B when used in conjunction with OmniOn's DC/DC bus converters recommended for ATCA applications. The following Figure 14 depicts the Class B EMI performance of PIM400F when tested with OmniOn's bus converter, QBVW033A0B1 with both modules mounted on the PIM400 Evaluation Board together with additional high frequency EMI capacitors (Fig 15).



**Figure 14. Typical Class B EMC signature of PIM400F as tested with OmniOn's bus converter, QBVW033A0B1 module.**



**Figure 15. PIM400 & QBVW033A0 Bus Converter Test setup schematic**

For Safety and noise considerations, copper traces must not be routed directly under the power module (PWB top layer). C\_EMI capacitors must make direct connections (preferably without vias) to the bus converter (DC/DC) module pins with as much copper width as possible. In case vias are necessary, allow for multiple connections to the inner plane with vias placed outside the footprint of the module. For additional layout guide-lines, refer to OmniOn's FLT012A0Z Input Filter Module data sheet.


### Safety Considerations

For safety agency approval the power module must be installed in compliance with the spacing and separation requirements of the end-use safety agency standards, i.e., UL ANSI/UL\* 62368-1 and CAN/CSA+ C22.2 No. 62368-1 Recognized, DIN VDE 0868- 1/ A11:2017 (EN62368-1:2014/A11:2017) The power input to these units is to be provided with a maximum of fast acting 20A fuses with a voltage rating of at least 75Vdc. Refer to "Thermal Consideration" section for additional safety considerations.

### Thermal Considerations

The power modules operate in a variety of thermal environments; however, sufficient cooling should be provided to help ensure reliable operation. Considerations include ambient temperature, airflow, module power dissipation, and the need for increased reliability. A reduction in the operating temperature of the module will result in an increase in reliability. The thermal data presented here is based on physical measurements taken in a wind tunnel.

The thermal reference point, Tref, used in the specifications is shown in Figure 16. For reliable operation this temperature should not exceed 130°C. In addition, the output current of the module should not exceed the rated current for the module as listed in the Ordering Information table, or the derated current for the actual operating conditions as indicated in Figs. 17 & 18.




**Figure 16. Tref Temperature Measurement Location.**


## Technical Specifications (continued)

### Heat Transfer via Convection

Increased airflow over the module enhances the heat transfer via convection. Derating curves showing the maximum output current that can be delivered by each module versus local ambient temperature (TA) for natural convection and up to 2 m/s (400 lfm) forced airflow are shown in Figures 17 & 18. Please refer to the Application Note “Thermal Characterization Process For Open-Frame Board-Mounted Power Modules” for a detailed discussion of thermal aspects including maximum device temperatures.



**Figure 17. -48V Output Current Derating for the Module; Airflow in the Transverse Direction from Pin7 to Pin1; Vin =48V & 3.3V @ 1.5A.**



**Figure 18. 3.3V Output Current Derating for the Module; Airflow in the Transverse Direction from Pin7 to Pin1; Vin =48V & -48V Output current = 4A.**

### Layout Considerations

The power modules are low profile in order to be used in fine pitch system card architectures. As such, component clearance between the bottom of the power module and the mounting board is limited. Avoid placing copper areas on the outer layer directly underneath the power module. Also avoid placing via interconnects underneath the power module. Particular attention should be paid to the clearance area as noted in the Bottom View of the Mechanical Outline drawing. For additional layout guidelines, refer to FLT012A0Z Data Sheet.

### Process Considerations

#### Through-Hole Lead-Free Soldering Information

The RoHS-compliant, Z version, through-hole products use the SAC (Sn/Ag/Cu) Pb-free solder and RoHS-compliant components. The module is designed to be processed through single or dual wave soldering machines. The pins have a RoHS-compliant, pure tin finish that is compatible with both Pb and Pb-free wave soldering processes. A maximum preheat rate of 3°C/s is suggested. The wave preheat process should be such that the temperature of the power module board is kept below 210°C. For Pb solder, the recommended pot temperature is 260°C, while the Pb-free solder pot is 270°C max.

#### Reflow Lead-Free Soldering Information

The RoHS-compliant through-hole products can be processed with paste-through-hole Pb or Pb-free reflow process.

Max. sustain temperature : 245°C (J-STD-020C Table 4-2: Packaging Thickness >=2.5mm / Volume > 2000mm<sup>3</sup>),  
Peak temperature over 245°C is not suggested due to the potential reliability risk of components under continuous high temperature.

Min. sustain duration above 217°C : 90 seconds  
Min. sustain duration above 180°C : 150 seconds

Max. heat up rate: 3°C/sec

Max. cool down rate: 4°C/sec

In compliance with JEDEC J-STD-020C spec for 2 times reflow requirement

#### Pb-free Reflow Profile

BMP module will comply with J-STD-020 Rev. C (Moisture/Reflow Sensitivity Classification for Nonhermetic Solid State Surface Mount Devices) for both Pb-free solder profiles and MSL classification procedures. BMP will comply with JEDEC J-STD-020C specification for 2 times reflow requirement. The suggested Pb-free solder paste is Sn/Ag/Cu (SAC). The recommended linear reflow profile using Sn/Ag/Cu solder is shown in Figure 19.

# Technical Specifications (continued)

## MSL Rating

The modules have a MSL rating of 2a.

## Storage and Handling

The recommended storage environment and handling procedures for moisture-sensitive surface mount packages is detailed in J-STD-033 Rev. A (Handling, Packing, Shipping and Use of Moisture/Reflow Sensitive Surface Mount Devices). Moisture barrier bags (MBB) with desiccant are required for MSL ratings of 2 or greater. These sealed packages should not be broken until time of use. Once the original package is broken, the floor life of the product at conditions of  $\leq 30^{\circ}\text{C}$  and 60% relative humidity varies according to the MSL rating (see J-STD-033A). The shelf life for dry packed SMT packages will be a minimum of 12 months from the bag seal date, when stored at the following conditions:  $< 40^{\circ}\text{C}$ ,  $< 90\%$  relative humidity.




Figure 19. Recommended linear reflow profile using Sn/Ag/Cu solder.

## Post Solder Cleaning and Drying Considerations

Post solder cleaning is usually the final circuit-board assembly process prior to electrical board testing. The result of inadequate cleaning and drying can affect both the reliability of a power module and the testability of the finished circuit-board assembly. For guidance on appropriate soldering, cleaning and drying procedures, refer to OmniOn Board Mounted Power Modules: Soldering and Cleaning Application Note (AP01-056EPS).

For additional information, please contact your Sales representative for more details.

## Digital Feature Descriptions

Full featured modules are available with I<sup>2</sup>C Digital Interface (Option -K).

Modules with I2C capability monitor up to five analog parameters and six status bits identified below in Tables 1 and 2 respectively.

### Modules with I<sup>2</sup>C Option Features:

Data pointer value	Parameter	Description	Scaling Factor
1eh	STATUS_BITS	Digital Signals (See Table 2)	N/A
1Fh	V_HLDP	Holdup voltage w.r.t. -48_out	0.398 V/bits
21h	-48V_IOUT	-48_out current	0.094 A/bits
22h	-48V_AF	Voltage between -48V_AF and VRTN_AF	0.325 V/bits
23h	-48V_BF	Voltage between -48V_BF and VRTN_BF	0.325 V/bits
28h	TEMP	Module Temperature	(1.961 <sup>o</sup> C/bit) -50 <sup>o</sup> C

Table 1: Internal register memory map

Bit	Name	Description	Value	Translation
0	ENABLE_AF_ST ATUS	ENABLE_AF_Signal Status	0	ENABLE_AF IS Disabled
			1	ENABLE_AF IS Enabled
1	ENABLE_BF_ST ATUS	ENABLE_BF_Signal Status	0	ENABLE_BF IS Disabled
			1	ENABLE_BF IS Enabled
2	ALRAM_STATUS	ALARM signal status	0	ALARM not set
			1	ALARM is set
3	N/A	Reserved		
4	HLDP_STAUS	Holdup status	0	C_HLDP not connected
			1	C_HLDP is connected
5	HOTSWAP_STATUS	Holdup status	0	Hot swap switch is off
			1	Hot swap switch is on
6	-48VOUT_STATUS	-48v_OUT Undervoltage alarm status	0	-48V_OUT is below threshold
			1	-48V_OUT is above threshold
7	N/A	Reserved		

Table 2: Digital signals

Note: Bit 0=LSB, Bit 7=MSB

## Technical Specifications (continued)

### I<sup>2</sup>C Command Structure:


The I<sup>2</sup>C is a 2-wire interface supporting multiple devices and masters on a single bus. The connected devices can only pull the bus wires low and they never drive the bus high. The bus wires should be externally connected to a positive supply voltage via a pull-up resistor. When the bus is idle, both DAT and CLK are high. The max sink current supported on the I<sup>2</sup>C bus is 3.5mA.

Each device on the I<sup>2</sup>C bus is recognized by a unique address stored in that device. Devices can be classified as masters or slaves when performing data transfers. A master is a device which initiates a data transfer on the bus and generates clock signals to permit that transfer. At the same time, any device addressed is considered slave. The PIM400 always acts as a slave.

In PIM400 module, I<sup>2</sup>C interface is used for reporting critical parameters like input voltage, output current, holdup capacitor voltage and temperature data. The read protocol is shown in the Fig 20 below.

Address For write ( R/W = 0)	XYZ from Table 3	R ( Ω )
5 Eh	111	Open
5 Ch	110	100000
5 Ah	101	40200
58 h	100	20000
56h	011	10000
54h	010	4020
52h	001	2000
50h	000	Short

**Table 4: I<sup>2</sup>C Addressing**



\*not shaded because transfer direction of data and acknowledge bits depends on R/W bits.

**Fig 20: Typical I<sup>2</sup>C Read protocol**

### Address Structure:

7 bit Address + R/W bit

Four bits are fixed (0101), three bits (xyz) are variable,

8 bit Address		
0101	xyz*	R/W

**Table 3: Address structure**

and the least-bit is the read/

significant write bit.

### Address Selection:

The three bits (xyz) of the address are set with a single external resistor from the ADD (pin10) to LOGIC\_GND (pin 13). The 8 possible addresses are shown in Table 4 with the respective resistance values.




# Technical Specifications (continued)

## Mechanical Outline

Dimensions are in millimeters and [inches].

Tolerances: x.x mm ± 0.5 mm [x.xx in. ± 0.02 in.] (unless otherwise indicated)

x.xx mm ± 0.25 mm [x.xxx in ± 0.010 in.]




## Technical Specifications (continued)

### Recommended Pad Layout

Dimensions are in and millimeters [inches].

Tolerances: x.x mm ± 0.5 mm [x.xx in. ± 0.02 in.] (unless otherwise indicated)



x.xx mm ± 0.25 mm [x.xxx in ± 0.010 in.]

Pin No.	Signal Name	Pin No.	Signal Name
1	-48V_AF	10**	ADD
2	-48V_BF	11**	DAT
3	VRTN_AF	12**	CLK
4	VRTN_BF	13	LOGIC_GND
5	ENABLE_AF	14	ALARM
6	ENABLE_BF	15	-48V_OUT
7	SHELF_GND	16	TRIM_HLDP
8	+5V0	17	VRTN_OUT
9	+3V3	18	V_HLDP

\*\* Pins 10, 11 & 12 are present only on modules with I<sup>2</sup>C digital interface option (-K).

#### NOTES:

1. FOR 0.030" X 0.025" RECTANGULAR PIN, USE 0.050" PLATED THROUGH HOLE

## Technical Specifications (continued)


### Packaging Details

The modules are supplied as standard in the plastic trays shown in Figure below.

### Tray Specification

Material	Antistatic coated PVC
Max surface resistivity	$10^{12}\Omega/\text{sq}$
Color	Clear
Capacity	12 power modules
Min order quantity	24 pcs (1 box of 2 full trays + 1 empty top tray)

Each tray contains a total of 12 power modules. The trays are self-stacking and each shipping box for the modules will contain 2 full trays plus 1 empty hold down tray giving a total number of 24 power modules.



Notes:

1. All radius unspecified are R2.0mm
2. All angle unspecified are  $5^\circ$
3. Dimension unit: mm (L);  $A^\circ$ (A).

## Technical Specifications (continued)

### Ordering Information

Please contact your OmniOn Sales Representative for pricing, availability and optional features

Input Voltage	Current Rating	Auxiliary Output #1	Auxiliary Output #2	Options	Product codes	Ordering Codes
-36 to -75 Vdc	10A	3.3V/3.6A	5.0V/0.15A	-	PIM400Z	150019196
-36 to -75 Vdc	10A	3.3V/3.6A	5.0V/0.15A	I <sup>2</sup> C Digital Interface	PIM400KZ	150019197
-36 to -75 Vdc	10A	3.3V/3.6A	5.0V/0.15A	I <sup>2</sup> C Digital Interface & Short pins (3.68mm)	PIM400K6Z	150033384

Table 1. Device Code

Option	Device Code Suffix
Short pins: 3.68mm ± 0.25mm (0.145 in. ± 0.010 in.)	6
Short pins: 2.79mm ± 0.25mm (0.110 in. ± 0.010 in.)	8
I <sup>2</sup> C Digital Interface	K

Table 2. Device Options

Description	Product Code	Ordering Codes
PIM400 Evaluation Board	EVAL_PIM400	150030502
QBDW033A0B Series Power Modules; DC-DC Converters 36-75V <sub>dc</sub> Input; 8.1-13.2V <sub>dc</sub> Output; 33A Output Current	QBDW033A0B41Z	CC109159307
QBVW033A0B Series Power Modules; DC-DC Converters 36-75V <sub>dc</sub> Input; 8.1-13.2V <sub>dc</sub> Output; 33A Output Current	QBVW033A0B41Z	CC109165247

Table 3. Related Products

## Change History (excludes grammar & clarifications)

Revision	Date	Description of the change
11.4	05/10/2022	Updated format RoHS Standard
11.5	06/24/2022	Updated external cap rating typos
11.6	11/21/2023	Updated as per OmniOn template

**OmniOn Power Inc.**

601 Shiloh Rd.  
Plano, TX USA

[omnionpower.com](http://omnionpower.com)

We reserve the right to make technical changes or modify the contents of this document without prior notice. OmniOn Power does not accept any responsibility for errors or lack of information in this document and makes no warranty with respect to and assumes no liability as a result of any use of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of OmniOn Power. This document does not convey license to any patent or any intellectual property right. Copyright© 2023 OmniOn Power Inc. All rights reserved.