

SERIES: SDI65G-T | DESCRIPTION: AC-DC POWER SUPPLY

FEATURES


- up to 65 W continuous power
- Gallium nitride (GaN) technology
- USB power delivery (PD 3.0)
- universal input
- over current and short circuit protection
- certified to IEC 62368-1
- compact design
- custom design available



MODEL	output voltage	output current max	output power max	ripple and noise ¹ max	efficiency level
	(Vdc)	(A)	(W)	(mVp-p)	
SDI65G-P-T	5	3.0	15	100	VI
	9	3.0	27	180	VI
	12	3.0	36	240	VI
	15	3.0	45	300	VI
	20	3.25	65	360	VI

Notes: 1. At full load, nominal input, 20 MHz bandwidth oscilloscope, each output terminated with 0.1 μ F multilayer ceramic and 47 μ F low ESR electrolytic capacitors.

PART NUMBER KEY



INPUT

parameter	conditions/description	min	typ	max	units
voltage		90	100~240	264	Vac
frequency		47	50~60	63	Hz
current	at 230 Vac, full load			0.8	A
inrush current	at 230 Vac, full load, cold start			80	A
leakage current	at 240 Vac /50 Hz			0.25	mA
no load power consumption				0.1	W

OUTPUT

parameter	conditions/description	min	typ	max	units
load regulation	5 Vdc output		+6/-4		%
	9 Vdc output		±5		%
	12 Vdc output		±5		%
	15 Vdc output		±5		%
	20 Vdc output		±5		%
line regulation			±1		%
start-up time	0% ~ 90% of rated output voltage			3	s
rise time	5V ~ 90% of output voltage			0.275	s
hold-up time		8.3			ms

PROTECTIONS

parameter	conditions/description	min	typ	max	units
over voltage protection	continuous, hiccup				
	5 Vdc output	3.3		4.5	A
	9 Vdc output	3.3		4.5	A
	12 Vdc output	3.3		4.5	A
	15 Vdc output	3.3		4.5	A
	20 Vdc output	3.5		4.8	A
short circuit protection	continuous, auto recovery				

SAFETY & COMPLIANCE

parameter	conditions/description	min	typ	max	units
isolation voltage	input to output for 2 seconds, 10 mA max		3,000		Vac
safety approvals	certified to 62368-1: EN				
EMI/EMC	EN 55032 Class B FCC PART 15 Class B				
ESD	IEC 61000-4-2, contact ±4 kV, air ±8 kV				
radiated immunity	IEC 61000-4-3, 1KHz field strength: 3 V/M				
EFT/burst	IEC 61000-4-4, 1.0 kV on input AC power ports				
surge	IEC 61000-4-5, line to line ± 1kV (peak)				
MTBF	as per MIL-HDBK-217F, at 25°C	100,000			hours
RoHS	yes				

ENVIRONMENTAL


parameter	conditions/description	min	typ	max	units
operating temperature		0		40	°C
storage temperature		-20		85	°C
operating humidity	non-condensing	10		90	%
storage humidity	non-condensing	5		90	%

MECHANICAL

parameter	conditions/description	min	typ	max	units
dimensions	90 x 40 x 27				mm
inlet plug	IEC320/C6				
weight	without ac cord		300		g


MECHANICAL DRAWING

units: mm
tolerance: ±1.0 mm




DC CORD


units: mm




AC CORD (US)




NORTH AMERICA




EUROPE




UNITED KINGDOM




AUSTRALIA




CHINA




SOUTH KOREA



BRAZIL



SOUTH AFRICA



JAPAN




Table 1

AC INPUT	CORD LENGTH
North America	1,830 mm ±30
Europe	1,830 mm ±30
United Kingdom	1,830 mm ±50
Australia	1,830 mm ±50
China	1,830 mm ±50
South Korea	1,830 mm ±50
Brazil	1,830 mm ±50
South Africa	1,830 mm ±50
Japan	1,830 mm ±50

REVISION HISTORY

rev.	description	date
1.0	initial release	04/24/2025

The revision history provided is for informational purposes only and is believed to be accurate.



Headquarters
15575 SW Sequoia Pkwy #100
Portland, OR 97224
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.