


PRO ECO3 960W 24V 40A II
Weidmüller Interface GmbH & Co. KG

 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com


The new PROeco 2nd generation power supplies maximise the availability of automation applications. The twelve-part series offers standard functions: with high performance, efficiency and suitability for many systems. The three-colour LED makes service activities and the integration of PROeco devices particularly easy. The series is compatible with DC UPS, electronic load monitoring and diode modules and is suitable for setting up power management systems. The compact design suits space-constrained applications, such as flat control cabinets in the field.

General ordering data

Version	Power supply, switch-mode power supply unit, 24 V
Order No.	3025660000
Type	PRO ECO3 960W 24V 40A II
GTIN (EAN)	4099986952058
Qty.	1 items

PRO ECO3 960W 24V 40A II

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Approvals

Approvals



ROHS Conform

UL File Number Search [UL Website](#)

Certificate No. (cURus) E255651

Certificate no. (cULus) E258476

Dimensions and weights

Depth	150 mm	Depth (inches)	5.9055 inch
Height	130 mm	Height (inches)	5.1181 inch
Width	110 mm	Width (inches)	4.3307 inch
Net weight	2490 g		

Temperatures

Storage temperature	-40 °C...85 °C	Operating temperature	-25 °C...70 °C
Start-up	≥ -40 °C	Humidity	5...95 % rel. humidity, no condensation

Environmental Product Compliance

RoHS Compliance Status	Compliant with exemption
RoHS Exemption (if applicable/known)	6c, 7a, 7cl
REACH SVHC	Lead 7439-92-1, Lead monoxide 1317-36-8
SCIP	cc530c6d-a7ac-41ec-a2b4-caa3b47dbe25

Rated data UL

Certificate No. (cURus)	E255651
-------------------------	---------

Input

Connection system	Screw connection	
AC input voltage range	3 x 320...3 x 575 V AC / 2 x 360...2 x 575 V AC	
Recommended back-up fuse	6 A / DI, safety fuse 10 A, Char. B, circuit breaker 6...8 A, Char. C, circuit breaker	
Frequency range AC	45...65 Hz	
Rated input voltage	3 x 400...3 x 500 V AC (wide-range input)	
Surge protection	Varistor	
Input fuse	internal	
Wire connection method	Screw connection	
DC input voltage range	450...800 V DC	
Current consumption in relation to the input voltage	Voltage type	3-phase AC
	Input voltage	400 V
	Input current	1.59 A
	Voltage type	3-phase AC
	Input voltage	500 V
	Input current	1.29 A
	Voltage type	DC
	Input voltage	450 V
	Input current	2.28 A

PRO ECO3 960W 24V 40A II

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

	Voltage type	DC
	Input voltage	800 V
	Input current	1.29 A
Line regulation (typ.)	1 %	
Input electric strength, max.	AC/DC	
Nominal power consumption	1032.3 VA	
Inrush current (typ.)	12 A	
Load regulation (typ.)	1 %	
Start-up time, max.	1 s	

Output

Output power	960 W	
Max. residual ripple	<50 mVPP / bandwidth 20 MHz	
Connection system	Screw connection	
Rated output voltage	24 V DC	
Parallel connection option	yes, max. 3	
Overload protection	Yes	
Output voltage, max.	28 V	
Output voltage, min.	22 V	
Wire connection method	Screw connection	
Output voltage, note	(adjustable via potentiometer)	
Nominal output current for U _{nom}	40 A @ 55 °C	
Line regulation (typ.)	1 %	
Capacitive load	unrestricted	
Mains failure bridge-over time	Mains failure bridge-over time, min.	22 ms
	Input voltage type	AC
	Input voltage	400 V
	Output current	40 A
	Output voltage	24 V
	Mains failure bridge-over time, min.	21 ms
	Input voltage type	AC
	Input voltage	500 V
	Output current	40 A
	Output voltage	24 V
Protection against inverse voltage	Yes	
Continuous output current @ U _{Nominal}	25 A @ 70 °C	
Load regulation (typ.)	1 %	
Ramp-up time	≤ 100 ms	

General data

AC failure bridging time @ I _{nom}	> 20 ms at 3 x 500 V AC / > 20 ms at 3 x 400 V AC	
Degree of efficiency	Typ.: 92,6% @ 400 V AC, Typ.: 92,4% @ 480 V AC	
Humidity	5...95 % rel. humidity, no condensation	
Protection degree	IP20	
Surge voltage category	II	
Mounting position, installation notice	on terminal rail TS 35	
Housing version	Metal, corrosion resistant	
Protection against reverse voltages from the load	30...35 V DC	
Power factor	Power factor typical	0.94
	Input voltage	400 V
	Ambient temperature	25 °C
	Output power	960 W
Earth leakage current, max.	3.5 mA	
Power loss, idling	5 W	
Short-circuit protection	Yes	

PRO ECO3 960W 24V 40A II

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Power loss, nominal load 82 W

Protection against over-heating Yes

EMC / shock / vibration

Limiting of mains voltage harmonic currents EN 61000-3-2

Noise emission in accordance with EN55032 Class B

Shock resistance IEC 60068-2-27

30 g in all directions

Interference immunity test acc. to

EN 61000-4-2 (ESD),
EN 61000-4-3 (RS), EN
61000-4-4 (burst), EN
61000-4-5 (surge), EN
61000-4-6 (conducted),
EN61000-4-8 (Fields),
EN 61000-4-11
(Dips), IEC 61000-6-1,
IEC 61000-6-2, IEC
61000-6-3, IEC 61000-6-4

Vibration resistance IEC 60068-2-6 0.7 g

Insulation coordination

Surge voltage category II

Protection class I, with PE connection

Insulation voltage input / earth 3 kV

Pollution severity 2

Insulation voltage, input/output 4 kV

Insulation voltage output / earth 0.5 kV

Electrical safety (applied standards)

Electrical machine equipment Acc. to EN60204

Safety extra-low voltage

SELV acc. to IEC
61010-1, PELV acc. to IEC
61010-2-201

Safety transformers for switch-mode power supplies According to EN 61558-2-16

Connection data (input)

Connection system Screw connection

Screwdriver blade 0.8 x 4.0

Number of terminals 4 for L1/L2/L3/PE

Conductor cross-section, AWG/kcmil , max. 10 AWG

Conductor cross-section, AWG/kcmil , min. 20 AWG

Wire connection cross section, flexible (input), max. 4 mm²Conductor cross-section, flexible , min. 0.22 mm²Conductor cross-section, rigid , max. 6 mm²Conductor cross-section, rigid , min. 0.18 mm²

Tightening torque, min. 0.5 Nm

Stripping length (input) 8 mm

Tightening torque, max. 0.6 Nm

Connection data (output)

Connection system Screw connection

Conductor cross-section, AWG/kcmil , max. 8 AWG

Number of terminals 5 (+ + / - -)

Conductor cross-section, AWG/kcmil , min. 22 AWG

Conductor cross-section, flexible , max. 16 mm²Conductor cross-section, flexible , min. 0.5 mm²Conductor cross-section, rigid , max. 16 mm²Conductor cross-section, rigid , min. 0.5 mm²

Stripping length (output) 12 mm

Tightening torque, min. 1.2 Nm

Screwdriver blade 1.0 x 5.5

Tightening torque, max. 2.2 Nm

Connection data (signal)

Wire connection cross-section, flexible (signal), max. 1.5 mm²

Stripping length (Signal) 8 mm

Wire cross-section, AWG/kcmil , max. 14

Wire cross-section, solid , min. 0.2 mm²

PRO ECO3 960W 24V 40A II

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Wire cross-section, solid , max.	1.5 mm ²	Wire connection cross-section, flexible (signal), min.	0.2 mm ²
Number of terminals	2	Wire cross-section, AWG/kcmil , min.	28 mm ²

Signalling

Floating contact	Yes	LED green	Operating voltage OK
Contact load (NO contact)	max. 30 V DC / 1 A		

Guarantee

Time interval	2 years
---------------	---------

Classifications


ETIM 6.0	EC002540	ETIM 7.0	EC002540
ETIM 8.0	EC002540	ETIM 9.0	EC002540
ETIM 10.0	EC002540	ECLASS 9.0	27-04-07-01
ECLASS 9.1	27-04-07-01	ECLASS 10.0	27-04-07-01
ECLASS 11.0	27-04-07-01	ECLASS 12.0	27-04-07-01
ECLASS 13.0	27-04-07-01	ECLASS 14.0	27-04-07-01
ECLASS 15.0	27-04-07-01		

PRO ECO3 960W 24V 40A II

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com


Drawings



Pay attention to polarity of DC connection

Status indicator and status relay

Operational status	Status LED	Relay contact (NO)
Fault-free operation: $U_{OUT} > 90\%$ of the set voltage	green	closed
Fault: $U_{OUT} \leq 85\%$ of the set voltage	red	opened
Overload pre-warning: $I_{OUT} > 90\% I_N$ (tolerance: $\pm 5\%$) and $U_{OUT} > 90\%$ of the set voltage	yellow	closed



PRO ECO3 960W 24V 40A II

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Accessories

Slotted screwdriver



VDE insulated screwdriver sets, for working on live parts up to 1000 V AC and 1500 V DC, DIN EN 60900. IEC 900. Each piece is "GS" safety tested. Blade made from fully hardened, high-alloy chromium-vanadium-molybdenum steel, gun-metal finish.

General ordering data

Type	SDIS SLIM 0.6X3.5X100	Version
Order No.	2749610000	Mounting tool, Blade width (B): 3.5 mm, Blade length: 100 mm, Blade
GTIN (EAN)	4050118896350	thickness (A): 0.6 mm
Qty.	1 ST	

Crosshead screwdriver, Pozidrive



VDE insulated screwdriver sets, for working on live parts up to 1000 V AC and 1500 V DC, DIN EN 60900. IEC 900. Each piece is "GS" safety tested. Blade made from fully hardened, high-alloy chromium-vanadium-molybdenum steel, gun-metal finish.

General ordering data

Type	SDIK SLIM PZ1 X 80	Version
Order No.	2749670000	Screwdriver, Blade width (B): 1 mm, 80 mm, Blade thickness (A): 1
GTIN (EAN)	4050118896411	
Qty.	1 ST	

End bracket



Weidmüller's range of products includes end brackets that guarantee a permanent, reliable mounting on the terminal rail and prevent sliding. Versions with and without screws are available. The end brackets include marking options, also for group markers, and also a test plug holder.

General ordering data

Type	WEW 35/1 V0 GF SW	Version
Order No.	1478990000	End bracket, black, TS 35, V-0, Wemid, Width: 12 mm, 130 °C
GTIN (EAN)	4050118286892	
Qty.	50 ST	

PRO ECO3 960W 24V 40A II

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Accessories

Type	WEW 35/2 V0 GF SW	Version
Order No.	1479000000	End bracket, black, TS 35, V-0, Wemid, Width: 8 mm, 130 °C
GTIN (EAN)	4050118286779	
Qty.	50 ST	
Type	WEW 35/1 SW	Version
Order No.	1162600000	End bracket, black, TS 35, V-2, Wemid, Width: 12 mm, 100 °C
GTIN (EAN)	4032248972630	
Qty.	50 ST	

Installation

Mounting accessory for Weidmüller Power Supplies.

General ordering data

Type	MTA 45 MF	Version
Order No.	1251310000	Electronics housings, Mounting flange
GTIN (EAN)	4050118042719	
Qty.	1 ST	