

TW5394 Datasheet


TW5394 Smart GNSS Antenna for Precise Positioning and Heading

Overview

The TW5394 is a multi-band (L1/L2), multi-constellation integrated GNSS receiver/antenna with integrated L-Band receiver for PointPerfect Flex PPP-RTK corrections. The TW5394 is capable of providing sub 1 meter accuracy stand alone, sub 6 cm accuracy with PPP-RTK corrections and sub 1 cm with RTK corrections to support the most demanding navigation, automation and precision mobility applications. Two TW5394's may be combined as a Moving Base RTK Precise Heading base and rover pair.

Interference Resilience

The TW5394 incorporates a latest generation multi-band (L1/L2) GNSS receiver with a Tallysman Accutenna® multi-band (L1/L2/Lband) triple band dual feed patch. The state of the art GNSS receiver supports concurrent tracking of all four major constellations (GPS, BeiDou, Galileo and GLONASS) in multiple frequency bands. The multi-band (L1/L2) architecture is highly effective method for the removal of ionospheric error. The TW5394 employs multi-stage filtering with low noise figure LNAs, combined with the dual feed Accutenna®, which greatly improves the rejection of multi-path signal interference.



Precise Point Positioning

The TW5394 offers support for a broad range of corrections services (RTCM RTK, networked PPP-RTK or PointPerfect Flex PPP-RTK over L-Band) allowing performance optimization according to each application's unique requirements. The concurrent multi-band (L1/L2) access to all four satellite constellations improves the receiver's convergence capability to deliver a quick, precise and reliable position solution which is resilient to ionospheric errors and improves resilience against interference and jamming.

The TW5394 may also be configured to operate in an RTK mode as either a base or rover for sub cm precision. For Precise Heading applications, two TW5394's may be arranged as a moving base RTK base and rover pair. The base device may receive PPP-RTK corrections for increased positional accuracy while concurrently sending RTCM correction messages to the rover.

Features:

- Improved noise immunity with multi-band u-blox ZED F9P GNSS receiver
- PointPerfect Flex PPP-RTK (networked and L-Band)
- Improved multi-path rejection with Dual feed Accutenna®
- Multi-band GNSS receiver is resilient to ionospheric errors
- High reliability timing with expansive constellation array
- Moving base RTK Precise Heading base/rover pair
- Exceptional position performance standalone without correction services
- 5V operation
- RS-422 differential (or RS-232) signalling
- Industrial grade IP69K enclosure
- Rugged fixed mount
- Multiple cable lengths (5m, 15m and 25m)
- Available with conical radome

TW5394 Datasheet

CALIAN
Confidence. Engineered.

TW5394 Smart GNSS Antenna for Precise Positioning and Heading

Specifications

Antenna	
Architecture	Multi-band (L1/L2), Dual Feed
Axial Ratio	L1: <1 dB typical.
Frequencies	GPS L1C/A L2C, GLO L1OF L2OF, GAL E1B/C E5b, BDS B1I B2I, QZSS L1C/A L2C
SBAS L1C/A	WAAS, EGNOS, MSAS, GAGAN
Channels	184-channel u-blox F9 engine
Anti-jamming	Active CW detection
Corrections Receiver	L-Band PPP-RTK (SSR)
Interface	
Pwr, Gnd	
33-5394-09-yy-zz	Data, Timepulse: RS-422 levels
33-5394-29-yy-zz	Data: RS-232; Timepulse: RS-422
Serial Protocol	
Output	NMEA 0183, UBX Binary, RTCM v3.3, SPARTN v2.0
Baud Rate	Configurable
Update Rate	9 Hz (4); 10 Hz (GPS+GAL+BDS); 20 Hz (GPS+GAL); 20 Hz (GPS+GLO); 16 Hz (GP+BDS); 25 Hz (GPS)
Mechanical	
Dimensions	66.5 mm dia. x 21 mm H
Weight	135 g
Mounting Method	Industrial grade fixed Mount
Cable Length	5, 15, 25m with RJ45 termination
Electrical	
Voltages	5 VDC
Current	0.6 Watts (nominal operating) Measured @ 5VDC supply
Environmental	
Operating Temperature	-40°C to +85°C
Storage Temperature	-40°C to +85°C
Weatherproof	IP69K
Shock	Vertical axis 50G, other axis 30G 3 axis sweep - 15 min
Vibration	10-200 Hz log sweep 3G
Sensitivity	
Tracking & Nav	-160 dBm
Reacquisition	-160 dBm
Hot starts	-158 dBm
Cold starts	-147 dBm
Acquisition	
Cold start	25 sec
Aided start	3 sec
Reacquisition	2 sec
Horizontal Position Accuracy (4 Constellations)	
Standard PVT	1.5m CEP
Standard SBAS	1.0m CEP
Corrected RTK	0.01m + 1ppm CEP
Augmented SPARTN (PPP-RTK)	<0.06m CEP
SPARTN Convergence	<45 sec*
Heading	
Dynamic Heading Accuracy	0.3° (30 m/sec)
Timing	
Timing Accuracy	30 ns RMS

Ordering Information:

33-5394-09-yy-zz-PC0 (RJ45; Data and Timepulse: RS-422, PC0 = NMEA out, no adaptor cable.) (RJ45;
33-5394-29-yy-zz-PC0 Data: RS-232, Timepulse RS-422, PC0 = NMEA out, no adaptor cable.)

yy = Radome (00=grey conical, 10=grey low profile, 01=white conical, 11=white low profile)

zz = Cable length in meters. Standard is 5m. (15m and 25m are special order only)

33-5394-09-yy-zz-PC0 SDK Test Adaptor required for programming **33-0095-11**

33-5394-29-yy-zz-PC0 SDK Test Adaptor required for programming **33-0095-16**

About Calian

We keep the world moving forward. Calian® helps people communicate, innovate, learn and lead safe and healthy lives. Every day, our employees live our values of customer commitment, integrity, innovation and teamwork to engineer reliable solutions that solve complex problems. That's Confidence. Engineered. A stable and growing 40-year company, we are headquartered in Ottawa with offices and projects spanning North American, European and international markets. Visit calian.com to learn about innovative healthcare, communications, learning and cybersecurity solutions.