

am Mira050

Datasheet

Published by ams-OSRAM AG
Tobelbader Strasse 30, 8141 Premstaetten, Austria
Phone +43 3136 500-0
ams-osram.com
© All rights reserved

am OSRAM

Table of contents

1	General description	3
2	Specifications & special features	3
3	Applications	5
4	Block diagram	5
5	Ordering information	6
6	Revision information	7
7	Legal information	8

Mira050 0.5 MP NIR-enhanced high speed global shutter image sensor

1 General description

Mira050 is a compact 0.5 MP Near IR enhanced global shutter image sensor designed for 2D and 3D consumer and industrial machine vision applications. The sensor has a small 2.79 μm pixel size with high sensitivity made possible by a state of the art BSI technology. The sensor has a MIPI CSI-2 interface to allow easy interfacing with a plethora of processors and FPGAs. Due to its small size, configurability and high sensitivity both in visual as well as NIR, the Mira050 is well suited for 2D and 3D applications, which include Active Stereo Vision, Structured Light Vision and AR/VR. High sensitivity in NIR enables increased measurement range and allows overall system power consumption optimization which is key for battery powered consumer and industrial applications.

2 Specifications & special features

Table 1: Key specifications

Parameter	Value	Remark
Active pixels	576 (H) x 768 (V) CSP 600 (H) x 800 (V) Bare Die	On CSP the addressable area is 600 x 800 but only 576 x 768 is useable.
Pixel	2.79 μm x 2.79 μm	BSI stacked technology with high NIR sensitivity. Low noise and low cross talk
Optical format	1/7"	
Dimensions	2.25 mm x 2.75 mm – Die 2.29 mm x 2.83 mm – CSP	Active area 60% of total.
Shutter type	Voltage domain pipelined global shutter	Possibility of exposure of next image during readout of the previous image.
Quantum efficiency (QE)	94 / 56 / 36 %	550 / 850 / 940 nm Mono
Supported lens chief ray angle (CRA)	0° to 30°	Extra wide acceptance angle of the Mira050 pixel means any lens profile with these CRA values can be used.
ADC modes	8-bit 10-bit 10-bit HS 12-bit	

Parameter	Value	Remark
Max frames per second full resolution	120 fps	All ADC modes
Analog gain	1x → 4x step: 2x	12-bit 10-bit HS (Default mode)
	1x → 16x step: 2x	10-bit (Default mode)
	1x → 4x step: 3%	10-bit HS (Fine gain mode)
	1x → 32x step: 2x	8-bit (Default mode)
	1x → 16x step: 3%	8-bit (Fine gain mode)
Digital gain	1x → 16x step: 1/16x	8-bit 10-bit 10-bit HS 12-bit
Data interface	MIPI CSI-2 v1.3 DPHY v1.2 1 Data lane 1 Clock lane	1.5 Gbps with data scrambling support

Table 2: Special features


Features	Benefits
Programmable registers	Programming of window coordinates, timing parameters, exposure time, mirror, flipping, cropping
High sensitivity and NIR enhanced pixel	High sensitivity and compact pixel size achieved via state of the art BSI technology with NIR enhancement resulting in less power hungry illuminators
Context switching	Two register contexts for on the fly configuration changes
On-chip processing	Defect pixel detection and correction Image statistics generation Event detection In pixel background light cancellation Digital pixel binning Black sun protection Flexible ROI selection
On-chip advanced power management	Smart powering of on chip blocks with respect to frame rate and exposure time resulting in extended battery life
On-chip temperature sensor	Accurate temperature reading on junction temperature
Illumination synchronization trigger	Accurate timing between illumination and actual exposure

3 Applications

- Facial authentication for mobile devices and points of payments.
- Active stereo and structured light vision (Robotics and other applications).
- Eye, head, hand, environment tracking for AR/VR.

4 Block diagram

Figure 1: Functional blocks of Mira050



5 Ordering information

Product code	Ordering code	Package	Delivery form	Color filter	Delivery quantity
Mira050-2QM3D0	Q65113A8201	Reconstructed wafer (bare die)	R/W	None	Upon Request
Mira050-2QM1WB	Q65113A8197	CSP	CSP	None	Multiples of 120
Mira050-2QC3D0	Q65113A8203	Reconstructed wafer (bare die)	R/W	RGB	Upon Request
Mira050-2QC1WB	Q65113A8202	CSP	CSP	RGB	Multiples of 120
Mira050-2QI3D0	Q65113A8205	Reconstructed wafer (bare die)	R/W	RGB-IR	Upon Request
Mira050-2QI1WB	Q65113A8204	CSP	CSP	RGB-IR	Multiples of 120

Figure 2: Product code description

M	I	R	A	0	5	0	-	2	Q	M	1	W	B
Sensor Name: Mira	Resolution: 0.50 MP	Silicon Version	Pixel: Q = QE Enhanced	Chroma: M = Mono C = Color I = RGB-IR	µLens: 1 = Reduced microlens array 3 = Full microlens array	Package: D = Bare Die W = WLCSP	Glass Type: 0 = N/A B = AR Coated no protective film						

6 Revision information

Document status	Product status	Definition
Product Preview	Pre-development	Information in this datasheet is based on product ideas in the planning phase of development. All specifications are design goals without any warranty and are subject to change without notice
Preliminary Datasheet	Pre-production	Information in this datasheet is based on products in the design, validation or qualification phase of development. The performance and parameters shown in this document are preliminary without any warranty and are subject to change without notice
Datasheet	Production	Information in this datasheet is based on products in ramp-up to full production or full production which conform to specifications in accordance with the terms of ams-OSRAM AG standard warranty as given in the General Terms of Trade

Other definitions

Draft / Preliminary:

The draft / preliminary status of a document indicates that the content is still under internal review and subject to change without notice. ams-OSRAM AG does not give any warranties as to the accuracy or completeness of information included in a draft / preliminary version of a document and shall have no liability for the consequences of use of such information.

Short datasheet:

A short datasheet is intended for quick reference only, it is an extract from a full datasheet with the same product number(s) and title. For detailed and full information always see the relevant full datasheet. In case of any inconsistency or conflict with the short datasheet, the full datasheet shall prevail.

Changes from previous released version to current revision v5-00	Page
Removed unnecessary information from Ordering information	6
Added code description	6

- Page and figure numbers for the previous version may differ from page and figure numbers in the current revision.
- Correction of typographical errors is not explicitly mentioned.

7 Legal information

Copyright & disclaimer

Copyright ams-OSRAM AG, Tobelbader Strasse 30, 8141 Premstaetten, Austria-Europe. Trademarks Registered. All rights reserved. The material herein may not be reproduced, adapted, merged, translated, stored, or used without the prior written consent of the copyright owner.

Devices sold by ams-OSRAM AG are covered by the warranty and patent indemnification provisions appearing in its General Terms of Trade. ams-OSRAM AG makes no warranty, express, statutory, implied, or by description regarding the information set forth herein. ams-OSRAM AG reserves the right to change specifications and prices at any time and without notice. Therefore, prior to designing this product into a system, it is necessary to check with ams-OSRAM AG for current information. This product is intended for use in commercial applications. Applications requiring extended temperature range, unusual environmental requirements, or high reliability applications, such as military, medical life-support or life-sustaining equipment are specifically not recommended without additional processing by ams-OSRAM AG for each application. This product is provided by ams-OSRAM AG "AS IS" and any express or implied warranties, including, but not limited to the implied warranties of merchantability and fitness for a particular purpose are disclaimed.

ams-OSRAM AG shall not be liable to recipient or any third party for any damages, including but not limited to personal injury, property damage, loss of profits, loss of use, interruption of business or indirect, special, incidental or consequential damages, of any kind, in connection with or arising out of the furnishing, performance or use of the technical data herein. No obligation or liability to recipient or any third party shall arise or flow out of ams-OSRAM AG rendering of technical or other services.

Product and functional safety devices/applications or medical devices/applications:

ams-OSRAM AG components are not developed, constructed or tested for the application as safety relevant component or for the application in medical devices. ams-OSRAM AG products are not qualified at module and system level for such application.

In case buyer – or customer supplied by buyer – considers using ams-OSRAM AG components in product safety devices/applications or medical devices/applications, buyer and/or customer has to inform the local sales partner of ams-OSRAM AG immediately and ams-OSRAM AG and buyer and /or customer will analyze and coordinate the customer-specific request between ams-OSRAM AG and buyer and/or customer.

ams OSRAM RoHS and REACH compliance statements for semiconductor products

RoHS compliant: The term "RoHS compliant" means that semiconductor products from ams OSRAM fully comply with current RoHS directives, and China RoHS. Our semiconductor products do not contain any chemicals for all 6 substance categories plus additional 4 substance categories (per amendment [EU2015/863](#)) above the defined threshold limit in the Annex II.

REACH compliant: Semiconductor products from ams OSRAM are free of Substances of Very High Concern (SVHC) according Article 33 of the [REACH Regulation 2006/1907/EC](#); please refer to the Candidate List of Substances of ECHA [here](#).

Important information: The information provided in this statement represents ams OSRAM knowledge and belief as of the date that it is provided. ams OSRAM bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. We are undertaking efforts to better integrate information from third parties. ams OSRAM has taken and will continue to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. ams OSRAM and its suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

Headquarters

ams-OSRAM AG
Tobelbader Strasse 30
8141 Premstaetten
Austria, Europe
Tel: +43 (0) 3136 500 0

Please visit our website at [ams-osram.com](#)

For information about our products go to [Products](#)

For technical support use our [Technical Support Form](#)

For feedback about this document use [Document Feedback](#)

For sales offices and branches go to [Sales Offices / Branches](#)

For distributors and sales representatives go to [Channel Partners](#)